



4" DECOMPOSED GRANITE, STABILIZED OR UNSTABILIZED PER SPECS.
 INSTALL DECOMPOSED GRANITE IN TWO 2" LIFTS
 90% COMPACTED SUBGRADE

2" STABILIZED DECOMPOSED GRANITE
 2"-4" OF 3/4" CRUSHED ROCK, SEE SPECS.
 90% COMPACTED SUBGRADE

(B) DECOMPOSED GRANITE ON GRADE

(A) DECOMPOSED GRANITE WITH AGGREGATE BASE
 HIGH TRAFFIC OR BIKE PARKING AREAS

DECOMPOSED GRANITE, CONDITION A OR B PER SPECS. (SUBMIT SAMPLE OF BOTH D.G. AND STABILIZER FOR APPROVAL)
 HOLD 1/4" FROM TOP OF HEADER

REDWOOD 2 x 4, OR 2 X 6 (CONST. HEART), PER SPECS.

GALVANIZED #8 NAILS

2" MULCH LAYER, HOLD 1/2" FROM TOP OF HEADER

1/2" x 12" REDWOOD STAKE (4' O.C. MAX.)

90% COMPACTED SUBGRADE

DECOMPOSED GRANITE WITH REDWOOD HEATER

NTS